

COPYRIGHT:

ALL ARTWORK, PICTURES AND TEXTS ARE COVERED BY OUR COPY-RIGHT.

THEY MUST NOT BE COPIED FOR REPRODUCTION (E.G. ON CD-ROM DISKS OR INTERNET-SITES) OR USED IN THEIR ENTIRE FORM OR IN EXCERPTS WITHOUT OUR PREVIOUS WRITTEN AGREEMENT.

IF YOU ARE DOWNLOADING PDF-FILES FROM OUR INTERNET HOME-PAGE FOR YOUR PERSONAL USE, MAKE SURE TO CHECK FOR UPDATED VERSIONS.

WE CANNOT TAKE ANY LIABILITY WHATSOEVER FOR DOWNLOADED FILES, AS TECHNICAL DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.


COPYRIGHT:

DIESE DRUCKSCHRIFT UND ALLE IHRE BESTANDTEILE IST URHEBERRECHTLICH GESCHÜTZT.

ABBILDUNGEN, GRAFISCHE DARSTELLUNGEN, TEXTE ODER DIE DRUCKSCHRIFT INSGESAMT ODER IN TEILEN DÜRFEN NICHT OHNE VORHERIGE SCHRIFTLICHE GENEHMIGUNG NACHGEDRUCKT ODER SONST REPRODUZIERT WERDEN (Z. B. AUF CD-ROM ODER IM INTERNET).

WENN SIE DIESE PDF-DATEI FÜR IHREN PERSÖNLICHEN GEBRAUCH VON UNSERER INTERNET-SEITE KOPIERT HABEN, MÖCHTEN WIR DARAUF HINWEISEN, DASS ALLE DORT ZUR VERFÜGUNG GESTELLTEN DATEIEN OHNE JEDEN WEITERN HINWEIS AUF DEN NEUESTEN TECHNISCHEN STAND GEBRACHT WERDEN. DIE ÄNDERUNG VON TECHNISCHEN DATEN UND LIEFERUMFANG IST DAHER VORBEHALTEN.

JUNIOR



ARRI 

ARRI JUNIOR SERIES



The ARRI Junior series is ideal, not only for small studios, but also for portable use. The light weight and compact size makes it a universal tool for cramped conditions without compromising efficiency or lamp life.

The classic ARRI construction of strong and rust-resistant extruded and die cast aluminium makes the Junior ideal for outdoor use.

The ARRI Junior series features:

- excellent optical performance
- high efficiency
- compact size
- robust construction
- easy operation
- easy service access
- wide range
- extensive accessories



Variants:

- 150W in-line dimmer
- 150W-650W with ERCO Track adapter
- P.O. versions of 650W-5000W
- range of options and colours available

For further information: www.arri.com

ARRI Junior 150 150W




Colours:  

Manual: L0.79360.E L0.79370.E with dimmer
L0.79360.B L0.79370.F with switch

Technical Data:

Size (mm): 126H x 80W x 165L
Weight (kg): 0.7
Lamp: 150W, 7003
150W, A1/248
150W, 64502
Base: G6.35
Lens size (mm): 50


Light Output (lux):



Accessories:

4-leaf Barndoor L2.79380.0 

Diffuser Frame L2.79395.0 

Scrim Set L9.73466.0 

Snoot L2.79390.0 

Small Kit Stand LS.1 

ARRI Junior 300 Plus 300W




Colours:   

Manual: L0.79200.B L0.79205.B L0.79209.B L0.79201.B

Technical Data:


Size (mm): 184H x 140W x 159L
Weight (kg): 1.5
Lamp: 300W, CP81
Base: GY9.5
Lens size (mm): 80


Light Output (lux):



Accessories:

4-leaf Barndoor L2.79170.0 

Diffuser Frame L2.79190.0 

Scrim Set L9.79160.0 

Snoot L2.79180.0 

Small Kit Stand LS.1 

ARRI Junior 650 Plus 650W




Colours:   

Manual: L0.79400.B L0.79405.B L0.79401.B
P.O.: L0.79400.I L0.79405.I -

Technical Data:

Size (mm): 215H x 181W x 189L
Weight (kg): 2.7
Lamp: 650W, CP89
500W, CP82
300W, CP81
Base: GY9.5
Lens size (mm): 112


Light Output (lux):



Accessories:

4-leaf Barndoor L2.79470.0 

Diffuser Frame L2.79490.0 

Scrim Set L9.79460.0 

Snoot L2.79480.0 

Medium Kit Stand LS.2 

All heads come complete with 4-leaf barndoor and diffuser frame.
1000 lux gives correct exposure for 200ASA film with aperture f4 at 24fps 1/48th sec.
BP Biplane MP Monoplane
Photometric data according to ESTA standards.
Data normalised to nominal lamp lumens.

In order to maintain the highest standards, ARRI reserves the right to alter specifications without notice.
© ARRI (GB) Ltd

ARRI Junior 1000 Plus 1000W



Colours:




Manual: L0.79610.B L0.79615.B L0.79611.B

P.O.: L0.79610.I L0.79615.I -

Technical Data:

Size (mm): 266H x 225W x 258L
 Weight (kg): 4.5
 Lamp: 1000W, CP71, BP
 1000W, CP40, MP
 Base: G22
 Lens size (mm): 130

Light Output (lux):



Accessories:

4-leaf Barndoor
L2.79670.0




8-leaf Barndoor
L2.79700.0



Diffuser Frame
L2.79690.0



Scrim Set
L9.79660.0



Snoot
L2.79680.0



Large Kit Stand
LS.3



ARRI Junior 2000 2000W



Colours:




Manual: L0.81250.B L0.81255.B L0.81251.B

P.O.: L0.81250.I L0.81255.I -

Technical Data:

Size (mm): 327H x 290W x 305L
 Weight (kg): 6
 Lamp: 2000W, CP73, BP
 2000W, CP41, MP
 Base: G38
 Lens size (mm): 175

Light Output (lux):



Accessories:

4-leaf Barndoor
L2.79870.0




8-leaf Barndoor
L2.79900.0



Diffuser Frame
L2.79890.0



Scrim Set
L9.79860.0



Snoot
L2.79880.0



Cine Stand
LS.4



ARRI Junior 5000 5000W



Colours:




Manual: L0.79350.B L0.80005.B -

P.O.: L0.79350.I L0.80005.I L0.80001.I

Technical Data:

Size (mm): 438H x 370W x 375L
 Weight (kg): 12.5
 Lamp: 5000W, CP85, BP
 5000W, CP29, MP
 Base: G38
 Lens size (mm): 250

Light Output (lux):



Accessories:

4-leaf Barndoor
L2.80950.0




8-leaf Barndoor
L2.80960.0



Diffuser Frame
L2.80970.0



Scrim Set
L9.80980.0



Snoot
L2.80975.0



Outrig Diffuser Frame
L2.80990.0



Universal Steel Stand
LS.5



3 Section Wind-Up Stand
LS.087


ARRI Original Accessories

LS.635 Super Clamp, Quick Action
 LE.6000.A Spigot 16 mm
 LS.137CB Safety Cable

Photometric Calculator

www.arri.com
 > products > lighting > support

Track-mounted versions available



Special versions for use with ERCO track system. Includes adapter and mains cable.
 L1.79360.S Junior 150
 L1.79200.S Junior 300 Plus
 L1.79400.S Junior 650 Plus

Colour options:



ARNOLD & RICHTER CINE TECHNIK

Lichttechnik, Pulvermühle,
83071 Stephanskirchen
Tel +49 80 36 3009 84
Fax +49 80 36 3009 79



ARRI LIGHTING SOLUTIONS GMBH

AGASTR. 24
D-12489 BERLIN
Tel +49 (0) 30 678-233-0
Fax +49 (0) 30 678-233-99

ARRI ITALIA S.r.l.

Viale Edison 318,
20099 Sesto S. Giovanni, Milano
Tel +39 02-26 22 71 75
Fax +39 02-242 16 92

ARRI INC. NEW YORK OFFICE

617 Route 303
Blauvelt, NY 10913-1109
Tel +1 845-353-14 00
Fax +1 845-425-12 50

ARRI CANADA Ltd.

415 Horner Avenue, Unit 11,
Etobicoke, Ontario, M8W 4W3,
Tel +1 416-255 33 35
Fax +1 416-255 33 99



ARRI (GB) Limited

2 Highbridge, Oxford Road, Uxbridge, Middlesex UB8 1LX

Tel: +44 (0)1895 457000 **Fax:** +44 (0)1895 457001

Email: sales@arri-gb.com **Web:** www.arri.com